



INFRAFLOW

Series B - 40 Foot SPECIFICATION SHEET

GENERAL

Building	Building Type	Steel frame, skid mounted
	Dimensions	8' x 40'x 9.5'
	Weight	Approx 18,000 lbs.
	Lifting	Lifting Lugs
Airflow	Type of Airflow	Passive
	Intake/Exhaust Separation	Polyurethane Gasket
	Filter Qty	38
	Filter Specification	MERV 6
	Filter Style	Washable
	Louvers - Exhaust	Actuated
	Louvers - Intake	Manual
Racks	Style	Custom Aluminum
	Features	Built-in cable management

ELECTRICAL INFRASTRUCTURE

Electrical Equipment	Continuous Power Rating	1.4 MW
	Input Voltage	415-240V 3 Phase
	Main Breaker Type	Disconnects
	Main Breaker Qty	4
	Main Breaker Size	600A
Mining	Miner Count	360
	Miner Compatibility	S19 Similar
Power Distribution Units	Quantity	14
	Outlets	24
	Type	Managed
	Amperage	150A
	Main Breaker	150A
	Receptacle Protection	40A Per 2 Plugs
	Input - 3 Phase	415/240V
	Output Receptacles	C19 *
	*Different plugs available to accommodate specific miners	
Networking	Quantity	9
	Managed	1
	Unmanaged	8
	Cable Quantity	0
	Cable Type	CAT 5E

